

Cleanroom Facemask, 3 Layers, w/ Ear-loops

The 'Hansong' Facemask is a three-layer (3-Ply) pleated design facemask incorporating elasticated earloops. Constructed using a mix of Polyethylene / Polypropylene non-woven material for the inner and outer layer with a micro-denier filter which filtrates more than 98% of 0.3µm particulates. The facemask is low-linting and provides process protection from contamination with high levels of comfort, good breathability and particle filtration. The facemask is sonically bonded for strength and cleanliness and the nose piece enclosed is made from a PVC coated wire which is easily adjusted for comfort.

Key Attributes

- Three-layer (3ply) Facemask with ear-loops
- Incorporating a micro-denier filter which filtrates more than 98% of 0.3µm particles
- Adjustable nose wire
- Sonically bonded
- Constructed using a mix of Polyethylene / Polypropylene non-woven material
- Size: 180 x 90mm

Application

- ISO 5 (Class 100) Cleanrooms and critical environments, Semiconductor, Electronics Manufacturing and Food processing

Quality Standards

- Manufactured in a facility holding ISO 9001:2008
- EAN Code: 0 609792609707

Cleanroom classification

- Recommended for ISO5 (Class 100) cleanrooms
- Manufactured and packed in an ISO 4 (Class 10) Cleanroom

Particle Count / Test Method

- Helmke Drum Test (IEST-RP-CC 004.3)
- Particle @ 0.3µm <100

Storage Instructions

- Store in cool dry place (below 28°C) away from direct sunlight and heat

Shelf Life

- 36 months from date of manufacture

Material

- Inner and Outer Layers: Polypropylene / Polypropylene
- Ear loops: Polyester/Spandex
- Nose wire: PVC coated wire



Ordering Information

Product Code	Layers	Colour	Size	Weight	Masks/Pk	Pks/Carton
30SNR	3 Ply	White	180 x 90mm	2.77 g/sh	50	40

www.lynbond2000.com

Revision:2020(c)

Company Registration No 3407384 Registered in England and Wales as a Limited Company

Registered Office: Building 3, North London Business Park, Oakleigh Road South, London, N11 1GN

